#### **NEWTONIAN MECHANICS**

# a = acceleration $v = v_0 + at$ F = force $x = x_0 + v_0 t + \frac{1}{2}at^2$ f = frequency h = height J = impulse K = kinetic energy $\Sigma \mathbf{F} = \mathbf{F}_{net} = m\mathbf{a}$ k = spring constant $\ell = \text{ length}$ $F_{fric} \le \mu N$ m = mass N = normal forceF = forceN = normal force $a_c = \frac{v^2}{r}$ P = powerp = momentumr = radius or distance $\tau = rF\sin\,\theta$ T = period $\mathbf{p} = m\mathbf{v}$ t = timeU = potential energy $\mathbf{J} = \mathbf{F} \Delta t = \Delta \mathbf{p}$ v = velocity or speed $K = \frac{1}{2}mv^{2}$ $\Delta U_{g} = mgh$ $W = F\Delta r\cos\theta$ W = work done on a system x = position $\mu$ = coefficient of friction $\theta$ = angle $\tau$ = torque $P_{avg} = \frac{W}{\Delta t}$ $P = F v \cos \theta$ $\mathbf{F}_{s} = -k\mathbf{x}$ $U_s = \frac{1}{2}kx^2$ $T_s = 2\pi \sqrt{\frac{m}{k}}$ $T_p = 2\pi \sqrt{\frac{\ell}{g}}$ $T = \frac{1}{f}$ $F_G = -\frac{Gm_1m_2}{r^2}$ $U_G = -\frac{Gm_1m_2}{r}$ www.MrLiddell.com

ELECTRICITY	AND MAGNETISM
$F = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r^2}$	A = area B = magnetic field
F	C = capacitance
$\mathbf{E} = \frac{\mathbf{r}}{a}$	d = distance
9	E = electric field
$U_{E} = qV = \frac{1}{1} \frac{q_{1}q_{2}}{1}$	$\boldsymbol{\mathcal{E}} = \operatorname{emf}$
$L = 4\pi\epsilon_0 r$	F = force
E - V	I = current
$E_{avg} = -\frac{1}{d}$	$\ell = \text{length}$
$1  \mathbf{\nabla} \ a_i$	P = power
$V = \frac{1}{4\pi\epsilon_0} \sum \frac{\eta}{r_0}$	Q = charge
	q = point charge
$C = \frac{Q}{Q}$	R = resistance
C = V	r = distance
$\epsilon_0 A$	t = time
$C = \frac{0}{d}$	U = potential (stored) energy
1 1 2	V = electric potential or
$U_c = \frac{1}{2}QV = \frac{1}{2}CV^2$	potential difference
2 2	v = velocity or speed
$I_{avg} = \frac{\Delta Q}{\Delta t}$	$\rho$ = resistivity
$\Delta t$	$\theta$ = angle
$R = \frac{\rho\ell}{A}$	$\phi_m =$ magnetic flux
V = IR	
P = IV	
$C_p = \sum_i C_i$	
$\frac{1}{C_s} = \sum_i \frac{1}{C_i}$	
$R_s = \sum_i R_i$	
$\frac{1}{R_p} = \sum_i \frac{1}{R_i}$	
$F_B = q \upsilon B \sin \theta$	
$F_B = BI\ell\sin\theta$	
$B = \frac{\mu_0}{2\pi} \frac{I}{r}$	
$\phi_m = BA\cos\theta$	<u> </u>
$\boldsymbol{\varepsilon}_{avg} = -\frac{\Delta \phi_m}{\Delta t}$	PHYSICS
$\boldsymbol{\varepsilon} = B\ell \boldsymbol{v}$	11

## **TITAN TABLE OF EQUATIONS**

WAVES AND OPTICS

 $n_1 \sin \theta_1 = n_2 \sin \theta_2$ 

 $\sin \theta_C = \frac{n_2}{n_1}$ 

 $\frac{1}{s_i} + \frac{1}{s_0} = \frac{1}{f}$ 

 $M = \frac{h_i}{h_0} = -\frac{s_i}{s_0}$  $f = \frac{R}{2}$ 

 $d\sin\theta = m\lambda$ 

 $x_m \approx \frac{m\lambda L}{d}$ 

Rectangle

Triangle

Circle

A = bh

 $A = \frac{1}{2}bh$ 

d = separation= frequency or

h = height

L = distance

R = radius of

s = distancev = speedx = position $\lambda$  = wavelength

 $\theta$  = angle

A = area

b = base

h = height

 $\ell = \text{length}$ 

w = width

r = radius

V = volume

C = circumference

S = surface area

GEOMETRY AND TRIGONOMETRY

M = magnification m = an integer n = index of

focal length

refraction

curvature

f

 $v = f\lambda$ 

 $n = \frac{c}{v}$ 

### FLUID MECHANICS AND THERMAL PHYSICS

$P = P_0 + \rho g h$	A = area
	e = efficiency
$F_{buoy} = \rho V g$	F = force
	h = depth
$A_1 v_1 = A_2 v_2$	H = rate of heat
1	k = thermal con
$P + \rho gy + \frac{1}{2}\rho v^2 = \text{ const.}$	$K_{avg}$ = average kinet
$\Delta \ell = \alpha \ell_{\perp} \Delta T$	$\ell = \text{length}$
	L = thickness
$kA \Delta T$	M = molar mass
H =	n = number of
	N = number of
$P = \frac{F}{A}$	P = pressure
A	Q = heat transfe
$PV = nRT = Nk_BT$	system
	T = temperature
$K = \frac{3}{2}k_{\rm p}T$	U = internal energy
1 <sup>avg</sup> 2 <sup>wB</sup>	v = volume
$3RT = 3k_BT$	v = velocity or
$\int U_{rms} = \sqrt{M} = \sqrt{-\mu}$	$v_{rms} = $ root-mea
	velocit
$W = -P\Delta V$	W = work done
$\Delta U = Q + W$	y = neight $\alpha = \text{coefficient}$
	$\alpha = \text{coefficient}$
e = W	$\mu = mass of mc$
$ Q_H $	a = donsity
	p – density
$e_c = \frac{I_H - I_C}{T}$	
TATOMIC AND NUCLEAR	PHYSICS

$$K_{\text{max}} = hf - \phi$$

$$\lambda = \frac{h}{p}$$

$$\Delta E = (\Delta m)c^{2}$$
**STAHOUITZ**

E = hf = pc

A = area
e = efficiency
F = force
h = depth
H = rate of heat transfer
k = thermal conductivity
$K_{avg}$ = average molecular
kinetic energy
$\ell = \text{length}$
L = thickness
M = molar mass
n = number of moles
N = number of molecules
P = pressure
Q = heat transferred to a
system
T = temperature
U = internal energy
V = volume
v = velocity or speed
$v_{rms}$ = root-mean-square
velocity
W = work done on a system
y = height
$\alpha$ = coefficient of linear
expansion
$\mu = mass of molecule$
$\rho = \text{density}$
IYSICS
E = energy
f = frequency
K = kinetic energy

$$m = mass$$
  
 $p = momentum$ 

f

$$\lambda =$$
wavelength  
 $\phi =$ work function

$$A = \pi r^{2}$$

$$C = 2\pi r$$
Parallelepiped
$$V = \ell wh$$
Cylinder
$$V = \pi r^{2} \ell$$

$$V = \pi r^{2} \ell$$
$$S = 2\pi r \ell + 2\pi r^{2}$$

2.

$$V = \frac{4}{3}\pi r^3$$
$$S = 4\pi r^2$$

Right Triangle 
$$a^2 + b^2 = c^2$$

$$a' + b' =$$
  
 $\sin \theta = \frac{a}{c}$ 

 $\cos\theta = \frac{b}{c}$ 

 $\tan \theta = \frac{a}{b}$ 



www.MrLiddell.com